



382P

#### ISO 측정항목

단위 Unit: mm

Order Number	피치규격		날수 Flutes Z	산수 Teeth Zt	날경 Diameter		유효장 Effective Length L2	길이 LkL	전장 Overall Length	샙크 Shank Dia d
	Thread	Pitch			D0D2	D1				

#### 외부 급유형 (Without coolant)

4ETMA 0105 033 S04 M014	M1.4	0.3	4	2	0.61	0.95	1.05	3.3	0.17	45	4
4ETMA 0105 040 S04 M014	M1.4	0.3	4	2	0.61	0.95	1.05	4	0.17	45	4
4ETMA 012 037 S04 M016	M1.6~M1.8	0.35	4	2	0.65	1.04	1.2	3.7	0.195	45	4
4ETMA 012 045 S04 M016	M1.6~M1.8	0.35	4	2	0.65	1.04	1.2	4.5	0.195	45	4
4ETMA 0155 045 S04 M2	M2	0.4	4	2	0.94	1.4	1.55	4.5	0.23	45	4
4ETMA 0155 055 S04 M2	M2	0.4	4	2	0.94	1.4	1.55	5.5	0.23	45	4
4ETMA 020 055 S04 M025	M2.5~M2.6	0.45	4	2	1.16	1.85	2	5.5	0.345	45	4
4ETMA 020 0675 S04 M025	M2.5~M2.6	0.45	4	2	1.16	1.85	2	6.75	0.345	45	4
4ETMA 024 070 S06 M3	M3	0.5	4	2	1.37	2.17	2.4	7	0.4	60	6
4ETMA 024 085 S06 M3	M3	0.5	4	2	1.37	2.17	2.4	8.5	0.4	60	6
4ETMA 032 092 S06 M4	M4	0.7	4	2	1.74	2.88	3.2	9.2	0.57	60	6
4ETMA 032 112 S06 M4	M4	0.7	4	2	1.74	2.88	3.2	11.2	0.57	60	6
4ETMA 039 115 S06 M5	M5	0.8	4	2	2.21	3.61	3.9	11.5	0.7	60	6
4ETMA 039 144 S06 M5	M5	0.8	4	2	2.21	3.61	3.9	14.4	0.7	60	6
4ETMA 047 140 S06 M6	M6~M9	1	4	2	2.82	4.4	4.7	14	0.79	60	6
4ETMA 047 170 S06 M6	M6~M9	1	4	2	2.82	4.4	4.7	17	0.79	60	6
4ETMA 061 180 S08 M8	M8~M12	1.25	4	2	4	5.8	6.1	18	0.9	65	8
4ETMA 061 220 S08 M8	M8~M12	1.25	4	2	4	5.8	6.1	22	0.9	65	8
4ETMA 078 230 S08 M10	M10~M15	1.5	4	2	5.16	7.4	7.8	23	1.12	65	8
4ETMA 078 280 S08 M10	M10~M15	1.5	4	2	5.16	7.4	7.8	28	1.12	65	8
4ETMA 090 260 S10 M12	M12	1.75	4	2	6.2	8.6	9	26	1.2	80	10
4ETMA 090 330 S10 M12	M12	1.75	4	2	6.2	8.6	9	33	1.2	80	10
4ETMA 118 350 S12 M16	M16~M23	2	4	2	7.4	11.4	11.8	35	2	100	12
4ETMA 118 430 S12 M16	M16~M23	2	4	2	7.4	11.4	11.8	43	2	100	12

#### 내부 급유형 (With coolant)

4ETMA 047 140 S06 M6C	M6~M9	1	4	2	2.82	4.4	4.7	14	0.79	60	6
4ETMA 047 170 S06 M6C	M6~M9	1	4	2	2.82	4.4	4.7	17	0.79	60	6
4ETMA 061 180 S08 M8C	M8~M12	1.25	4	2	4	5.8	6.1	18	0.9	65	8
4ETMA 061 220 S08 M8C	M8~M12	1.25	4	2	4	5.8	6.1	22	0.9	65	8
4ETMA 078 230 S08 M10C	M10~M15	1.5	4	2	5.16	7.4	7.8	23	1.12	65	8
4ETMA 078 280 S08 M10C	M10~M15	1.5	4	2	5.16	7.4	7.8	28	1.12	65	8
4ETMA 090 260 S10 M12C	M12	1.75	4	2	6.2	8.6	9	26	1.2	80	10
4ETMA 090 330 S10 M12C	M12	1.75	4	2	6.2	8.6	9	33	1.2	80	10
4ETMA 118 350 S12 M16C	M16~M23	2	4	2	7.4	11.4	11.8	35	2	100	12
4ETMA 118 430 S12 M16C	M16~M23	2	4	2	7.4	11.4	11.8	43	2	100	12

**Inch 측정항목**

단위 Unit: mm

Order Number	피치규격		날수 Flutes Z	산수 Teeth Zt	날경			유효장 Effective Length L2	길이 LkL	전장 Overall Length	샙크 Shank Dia d
	Thread	Pitch			Diameter						
					D0D2	D1					
<b>외부 급유형 (Without coolant)</b>											
4ETMA 021 072 S06	NO.4-40	40	4	2	1	1.76	2.1	7.2	0.38	60	6
4ETMA 021 088 S06	NO.4-40	40	4	2	1	1.76	2.1	8.8	0.38	60	6
4ETMA 026 086 S06	NO.6-32	32	4	2	1.32	2.21	2.6	8.6	0.45	60	6
4ETMA 026 105 S06	NO.6-32	32	4	2	1.32	2.21	2.6	10.5	0.45	60	6
4ETMA 030 100 S06	NO.8-32	32	4	2	1.42	2.62	3	10	0.6	60	6
4ETMA 030 122 S06	NO.8-32	32	4	2	1.42	2.62	3	12.2	0.6	60	6
4ETMA 035 114 S06	NO.10-24	24	4	2	1.58	3.18	3.5	11.4	0.8	60	6
4ETMA 048 145 S06	1/4" x 20	20	4	2	2.69	4.29	4.8	14.5	0.8	60	6
4ETMA 048 180 S06	1/4" x 20	20	4	2	2.69	4.29	4.8	18	0.8	60	6
4ETMA 050 144 S06	1/4" x 28	28	4	2	3.2	4.58	5	14.4	0.69	60	6
4ETMA 050 178 S06	1/4" x 28	28	4	2	3.2	4.58	5	17.8	0.69	60	6

**내부 급유형 (With coolant)**

4ETMA 048 145 S08C	1/4" x 20	20	4	2	2.69	4.29	4.8	14.5	0.8	65	8
4ETMA 048 180 S08C	1/4" x 20	20	4	2	2.69	4.29	4.8	18	0.8	65	8
4ETMA 050 144 S08C	1/4" x 28	28	4	2	3.2	4.58	5	14.4	0.69	65	8
4ETMA 050 178 S08C	1/4" x 28	28	4	2	3.2	4.58	5	17.8	0.69	65	8
4ETMA 065 176 S08C	5/16"-24	24	4	2	4.34	6.02	6.5	17.6	0.85	65	8
4ETMA 065 218 S08C	5/16"-24	24	4	2	4.34	6.02	6.5	21.8	0.85	65	8
4ETMA 067 260 S08C	3/8"-16	16	4	2	3.98	6.18	6.7	26	1.1	65	8

## 4ETM Cutting Condition

피삭재 Material	합금강/ 공구강 Alloy Steel/ Tool Steel		고경도강 Hardened Steels		알루미늄 Aluminum		스테인레스강 Stainless Steel	
경도 Hardness	~ 30HRC		35 ~ 45HRC					
TAP	V/C	FZ	V/C	FZ	V/C	FZ	V/C	FZ
M3	50 ~ 70	0.01 ~ 0.02	45 ~ 55	0.005 ~ 0.01	100 ~ 130	0.03 ~ 0.04	70 ~ 80	0.015 ~ 0.025
M4	50 ~ 70	0.01 ~ 0.02	45 ~ 55	0.005 ~ 0.01	100 ~ 130	0.03 ~ 0.04	70 ~ 80	0.015 ~ 0.025
M5	50 ~ 70	0.01 ~ 0.02	45 ~ 55	0.005 ~ 0.01	100 ~ 130	0.03 ~ 0.04	70 ~ 80	0.015 ~ 0.025
M6	50 ~ 70	0.02 ~ 0.03	45 ~ 55	0.01 ~ 0.015	100 ~ 130	0.04 ~ 0.05	70 ~ 80	0.025 ~ 0.035
M8	50 ~ 70	0.02 ~ 0.03	45 ~ 55	0.01 ~ 0.015	100 ~ 130	0.04 ~ 0.05	70 ~ 80	0.03 ~ 0.04
M10	50 ~ 70	0.02 ~ 0.03	45 ~ 55	0.015 ~ 0.02	100 ~ 130	0.05 ~ 0.06	70 ~ 80	0.03 ~ 0.04
M12	50 ~ 70	0.03 ~ 0.04	45 ~ 55	0.02 ~ 0.025	100 ~ 130	0.06 ~ 0.07	70 ~ 80	0.03 ~ 0.04
M16	50 ~ 70	0.03 ~ 0.04	45 ~ 55	0.02 ~ 0.025	100 ~ 130	0.06 ~ 0.07	70 ~ 80	0.04 ~ 0.05

## 4MTM Cutting Condition

피삭재 Material	합금강/ 공구강 Alloy Steel/ Tool Steel		고경도강 Hardened Steels		알루미늄 Aluminum		스테인레스강 Stainless Steel	
경도 Hardness	~ 30HRC		35 ~ 45HRC					
TAP	V/C	FZ	V/C	FZ	V/C	FZ	V/C	FZ
M1	50 ~ 70	0.005 ~ 0.01	55 ~ 65	0.005 ~ 0.01	100 ~ 130	0.02 ~ 0.34	70 ~ 85	0.005 ~ 0.01
M2	50 ~ 70	0.005 ~ 0.01	55 ~ 65	0.005 ~ 0.01	100 ~ 130	0.02 ~ 0.34	70 ~ 85	0.005 ~ 0.01
M3	50 ~ 70	0.01 ~ 0.02	55 ~ 65	0.01 ~ 0.02	100 ~ 130	0.02 ~ 0.34	70 ~ 85	0.005 ~ 0.01
M4	50 ~ 70	0.01 ~ 0.02	55 ~ 65	0.01 ~ 0.02	100 ~ 130	0.04 ~ 0.05	70 ~ 85	0.01 ~ 0.02
M5	50 ~ 70	0.02 ~ 0.03	55 ~ 65	0.02 ~ 0.03	100 ~ 130	0.04 ~ 0.05	70 ~ 85	0.01 ~ 0.02
M6	50 ~ 70	0.02 ~ 0.03	55 ~ 65	0.02 ~ 0.03	100 ~ 130	0.05 ~ 0.06	70 ~ 85	0.02 ~ 0.03

## 4STM Cutting Condition

피삭재 Material	합금강/ 공구강 Alloy Steel/ Tool Steel		고경도강 Hardened Steels		알루미늄 Aluminum		스테인레스강 Stainless Steel	
경도 Hardness	~ 30HRC		35 ~ 45HRC					
TAP	V/C	FZ	V/C	FZ	V/C	FZ	V/C	FZ
M3	50 ~ 70	0.01 ~ 0.02	55 ~ 65	0.008 ~ 0.01	100 ~ 130	0.03 ~ 0.04	70 ~ 85	0.01 ~ 0.02
M4	50 ~ 70	0.01 ~ 0.02	55 ~ 65	0.008 ~ 0.01	100 ~ 130	0.03 ~ 0.04	70 ~ 85	0.01 ~ 0.02
M5	50 ~ 70	0.01 ~ 0.02	55 ~ 65	0.01 ~ 0.02	100 ~ 130	0.03 ~ 0.04	70 ~ 85	0.01 ~ 0.02
M6	50 ~ 70	0.01 ~ 0.02	55 ~ 65	0.01 ~ 0.02	100 ~ 130	0.04 ~ 0.05	70 ~ 85	0.02 ~ 0.03
M8	50 ~ 70	0.02 ~ 0.03	55 ~ 65	0.02 ~ 0.03	100 ~ 130	0.04 ~ 0.05	70 ~ 85	0.02 ~ 0.03
M10	50 ~ 70	0.02 ~ 0.03	55 ~ 65	0.02 ~ 0.03	100 ~ 130	0.05 ~ 0.06	70 ~ 85	0.03 ~ 0.04
M12	50 ~ 70	0.02 ~ 0.03	55 ~ 65	0.02 ~ 0.03	100 ~ 130	0.06 ~ 0.07	70 ~ 85	0.05 ~ 0.06
M16	50 ~ 70	0.03 ~ 0.04	55 ~ 65	0.03 ~ 0.04	100 ~ 130	0.06 ~ 0.07	70 ~ 85	0.05 ~ 0.06

## 4HTM Cutting Condition

피삭재 Material	합금강/ 공구강 Alloy Steel/ Tool Steel		고경도강 Hardened Steels		알루미늄 Aluminum		스테인레스강 Stainless Steel	
경도 Hardness	~ 30HRC		35 ~ 45HRC					
TAP	V/C	FZ	V/C	FZ	V/C	FZ	V/C	FZ
M3	50 ~ 70	0.01 ~ 0.02	50 ~ 60	0.005 ~ 0.008	100 ~ 130	0.03 ~ 0.04	70 ~ 85	0.01 ~ 0.02
M4	50 ~ 70	0.01 ~ 0.02	50 ~ 60	0.005 ~ 0.008	100 ~ 130	0.03 ~ 0.04	70 ~ 85	0.01 ~ 0.02
M5	50 ~ 70	0.01 ~ 0.02	50 ~ 60	0.01 ~ 0.02	100 ~ 130	0.03 ~ 0.04	70 ~ 85	0.01 ~ 0.02
M6	50 ~ 70	0.01 ~ 0.02	50 ~ 60	0.01 ~ 0.02	100 ~ 130	0.04 ~ 0.05	70 ~ 85	0.02 ~ 0.03
M8	50 ~ 70	0.02 ~ 0.03	50 ~ 60	0.02 ~ 0.03	100 ~ 130	0.04 ~ 0.05	70 ~ 85	0.02 ~ 0.03
M10	50 ~ 70	0.02 ~ 0.03	50 ~ 60	0.02 ~ 0.03	100 ~ 130	0.05 ~ 0.06	70 ~ 85	0.03 ~ 0.04
M12	50 ~ 70	0.02 ~ 0.03	50 ~ 60	0.02 ~ 0.03	100 ~ 130	0.06 ~ 0.07	70 ~ 85	0.05 ~ 0.06
M16	50 ~ 70	0.03 ~ 0.04	50 ~ 60	0.03 ~ 0.04	100 ~ 130	0.06 ~ 0.07	70 ~ 85	0.05 ~ 0.06

- 가급적 열박음 척을 추천합니다.
- 공구 진입시 이송 f (mm/tooth)를 나사가공 이송 대비 30% 수준으로 낮춰 주십시오.
- 상기 절삭조건은 참고 수치이므로, 실 가공시 가공 형상, 가공 목적, 적용 기계에 따라 조건변경 요망 합니다.
- 절삭시 내,외부 급유형 쿨런트 사용을 추천합니다.
- Using shrink-fit chuck is recommended.
- When the tool approaches the work material, reduce the feed by 30%.
- Use this table for your reference. Adjust the parameters depending on your machining geometry, machining purpose and CNC.
- Internal and external coolants are recommended for milling.

# Your specials are our standards.

## 당신의스페셜은우리의표준품입니다.

WWW.JJTOOLS.CO.KR

**LONG Life HIGH Performance**

www.jjtools.co.kr

**FINISHING: 초경 장삭형 인서트 TSPM-S**

**INSETS**

New Products

Your specials are our standards.

**LOW Price HIGH Performance**

www.jjtools.co.kr

**FLAT DRILL**

가려만족, 성능만족 - 다기능 플랫드릴 시리즈

**NEW**

Price Satisfaction, Performance Satisfaction - Multi functional Flat Drill Series

Your specials are our standards.

**45TM 시리즈 20TM**

공구 교체없이 드릴링, 나사가공, 챔퍼가공을 한번에 -

**THREAD MILLS**

Drilling, threading and chamfering in one tool operation

45TM Series, 20TM Series, 45TM Series, 20TM Series

Your specials are our standards.

**DENTAL SERIES**

www.jjtools.co.kr

정밀 제조시엔 CAD/CAM Milling Bur

RECLAND, VMP, ALPINE, PROXODIUM, MET-COAT, ALUMINUM OXIDE, SPINUM

Your specials are our standards.

**나노 다이아몬드 코팅!**

Strong & Long Lasting New Diamond Coating

흡착현상을 최소화!

Minimize built-up edge by new diamond coating

**For Composite Materials**

Your specials are our standards.